

MAINTENANCE CHECK SHEET 2010MY-Onwards LR4 (LA)

										_		
MAINTENANCE	• TIME (Years)	1	2	3	4	5	6	7	8	9	10	
	 MILES (Thousands) 	15	30	45	60	75	90	105	120	135	150	
	 KM (Thousands) 	24	48	72	96	120	144	168	192	216	240	
• See Passport to Service for additional information												
1. VEHICLE INTERIOR												
Reset Service Interval and Engine Oil Level indicators												
Check operation of all lights, warning indicators and horn												
Check operation of front / rear wiper washer systems; inspect blades												
Check operation of electric park brake												
Check condition and security of seats and seat belts												
2. VEHICLE EXTERIOR		-		1			1	1				
		_				_				_		
Check all tire pressures, condition, and tread depth												
3. ENGINE COMPARTME	ENT											
Check battery condition, fill electrolyte, clean terminals												
Check and top up: brake, PAS and windshield washer fluid												
Check engine coolant level and freeze protection level												
Inspect drive belt(s)												
Replace engine oil and replace filter												
Replace pollen filter												
Replace air-cleaner elements *												
Replace brake fluid *		Ev	Every 3 years									
Replace spark plugs *		Every 105,000 mi / 168,000 km										
Replace accessory drive belt *		Ev	Every 150,000 mi / 240,000 km									
Replace engine coolant *		Ev	Every 10 years									
4. UNDER VEHICLE												
Check for fluid leaks												
Check condition / operation of suspension and steering components, boots, and drive axles												
Check brake, fuel lines, PAS hoses and unions for correct routing and damage												
Remove road wheels; lubricate wheel centers												
Inspect for brake pad wear, caliper leaks and disc condition												
Install road wheels to opposite side of the vehicle												
	Replace transfer case fluid; replace drain and fill plug washers *											
Replace locking differential												
Replace flexible brake hoses *		Every 6 years										
Replace front and non-locking rear differential fluid *			Every 10 years									
Replace fuel filter *		Every 10 years / 150,000 mi / 240,000 km										
Replace automatic transmission fluid *			Every 10 years / 150,000 mi / 240,000 km									
				youro ,	100,00		- 10,000					
	ERVICE CAMPAIGN NEEDED											
Check for open Service Campaigns / Recalls												
If fault lamps illuminated use IDS to find the faults and report												
6. ROAD TEST												
Select LOW range; move vehicle 60 ft (18 m); select HIGH range												
Road test vehicle												
Record performance of Service in Passport to Service												
Record performance of Service in Passport to Service			I –									

* Labor cost not included in scheduled time

NOTIFICATION OF SERVICE REQUIREMENTS:

Please refer to your Owner's Manual for Service Recommendations if your vehicle is used extensively off-road or under severe conditions.
 The owner or operator is responsible for Owner Checks listed in the Owner's Manual. These are *not* included in the Service Schedule.